



## ECO PREMIUM RANGE 20W LED FLOODLIGHT WITH PIR MOTION SENSOR

961-023 CYFELCO 2 FLL 20W WHITE 840 MLS

### PRODUCT DATASHEET

LED FLOODLIGHT SUITABLE FOR OUTDOOR INSTALLATION

---

#### Areas of application

- Direct replacement for conventional floodlights with halogen lamps
- Public areas, Building Facades, Construction areas
- Gardens, balconies and other outdoor areas
- Parking area lighting

---

#### Product Features

- Premium performance with CRI (Ra)>80 and 100 lm/W
- Energy Class E
- Flicker-free design
- Aluminium Housing and Clear Glass Diffuser
- Lifetime (L70/B50): up to 25,000 h (at 25 °C)
- 3 Years Warranty



Agios Adrianos, 21100 Nafplio Greece / Europe  
Tel. +302752 091136 | [elmasco@elmasco.eu](mailto:elmasco@elmasco.eu) | [www.elmasco.eu](http://www.elmasco.eu)

LIGHT  
RIGHT

# TECHNICAL DATA

## Operating and Electrical

Input Voltage	220-240V AC
Line Frequency	50/60 Hz
Nominal Power Consumption	20W
Power Factor	>0.9
Total Harmonic Distortion	<20%
Protection Class	Class I
Driver	DOB
Photobiological safety group	RG 1

## Application

Ambient Temperature Range	-20 to +40 °C
Ingress Protection Code	IP65
Mech. Impact Protection	IK06
Mounting Type	Mounting Bracket
Dimmable	No

## Logistics (Packaging)

Product Dimensions (H x L x W)	24.5x114.3x80.3mm
Packaging Size	171x50x119 mm
Packing	1 pcs per carton box
Gross Weight	0.261 kg
Net Weight	0.217 kg
Volume	0.001 m <sup>3</sup>

## Directives

2014/30/EU	Electromagnetic Compatibility Directive
2014/35/EU	Low Voltage Directive
2011/65/EU	Restriction of Hazardous Substances Directive (RoHS)
2009/125/EU	Ecodesign Requirements for energy-related products

## Standards

EN 60598-1:2015	Luminaires part 1: General Requirements
EN 60598-2-1:1989	Luminaires Part 2: Particular requirements-Section 1 Fixed general purpose luminaires
EN IEC 55015:2019+A11:2020	Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment
EN 61547:2009	Equipment for general lighting purposes - EMC immunity requirements
EN IEC 61000-3-2:2019	Electromagnetic compatibility (EMC) - Part 3-2: Limits - Limits for harmonic current emissions (equipment input current ≤16 A per phase)
EN 61000-3-3:2013+A1:2019	Electromagnetic compatibility (EMC) - Part 3-3: Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection

## Photometric Data

Luminous Flux	2000 lm
Luminous Efficacy	100 lm/W
Color Temperature	4000 K (Cool White)
Color Rendering Index Ra	>80
SDCM	<5
Beam Angle	110°
Flickering metric (Pst LM)	<1
Stroboscopic Effect (SVM)	<4

## Mechanical and Housing

Housing Material	Aluminium
Diffuser	Clear Glass
Housing Color	White

## Overtime Performance

Lifespan L70/B50 at 25 °C	> 25,000 hrs
---------------------------	--------------

## Logistics (Master Box)

Master Box Size	365x270x260 mm
Packing	20pcs per Master Box
Master Box Gross Weight	5.3 kg
Master Box Net Weight	4.34 kg
Volume	0.0256 m <sup>3</sup>

