



ECO PREMIUM RANGE 30W LED FLOODLIGHT

961-027 CYFELCO 2 FLL 30W BLACK 865

PRODUCT DATASHEET

LED FLOODLIGHT SUITABLE FOR OUTDOOR INSTALLATION

Areas of application

- Direct replacement for conventional floodlights with halogen lamps
- Public areas, Building Facades, Construction areas
- Gardens, balconies and other outdoor areas
- Parking area lighting

Product Features

- Premium performance with CRI (Ra)>80 and 120 lm/W
- Energy Class E
- Flicker-free design
- Aluminium Housing and Clear Glass Diffuser
- Lifetime (L70/B50): up to 25,000 h (at 25 °C)
- 3 Years Warranty



TECHNICAL DATA

Operating and Electrical

Input Voltage	220-240V AC
Line Frequency	50/60 Hz
Nominal Power Consumption	30W
Power Factor	>0.9
Total Harmonic Distortion	<20%
Protection Class	Class I
Driver	DOB
Photobiological safety group	RG 1

Application

Ambient Temperature Range	-20 to +40 °C
Ingress Protection Code	IP65
Mech. Impact Protection	IK06
Mounting Type	Mounting Bracket
Dimmable	No

Logistics (Packaging)

Product Dimensions (H x L x W)	25x143.6x100mm
Packaging Size	153x29x118 mm
Packing	1 pcs per carton box
Gross Weight	0.276 kg
Net Weight	0.243 kg
Volume	0.0005 m ³

Directives

2014/30/EU	Electromagnetic Compatibility Directive
2014/35/EU	Low Voltage Directive
2011/65/EU	Restriction of Hazardous Substances Directive (RoHS)
2009/125/EU	Ecodesign Requirements for energy-related products

Standards

EN 60598-1:2015	Luminaires part 1: General Requirements
EN 60598-2-1:1989	Luminaires Part 2: Particular requirements-Section 1 Fixed general purpose luminaires
EN IEC 55015:2019+A11:2020	Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment
EN 61547:2009	Equipment for general lighting purposes - EMC immunity requirements
EN IEC 61000-3-2:2019	Electromagnetic compatibility (EMC) - Part 3-2: Limits - Limits for harmonic current emissions (equipment input current ≤16 A per phase)
EN 61000-3-3:2013+A1:2019	Electromagnetic compatibility (EMC) - Part 3-3: Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection

Photometric Data

Luminous Flux	3600 lm
Luminous Efficacy	120 lm/W
Color Temperature	6500 K (Cool Daylight)
Color Rendering Index Ra	>80
SDCM	<5
Beam Angle	110°
Flickering metric (Pst LM)	<1
Stroboscopic Effect (SVM)	<4

Mechanical and Housing

Housing Material	Aluminium
Diffuser	Clear Glass
Housing Color	Black

Overtime Performance

Lifespan L70/B50 at 25 °C	> 25,000 hrs
---------------------------	--------------

Logistics (Master Box)

Master Box Size	320x175x260 mm
Packing	20pcs per Master Box
Master Box Gross Weight	5.6 kg
Master Box Net Weight	4.86 kg
Volume	0.0146 m ³

