

OFFICE COMPLIANT RECESSED LED LUMINAIRE

CYFELCO REC 2LNS 23W 3980LM 4000K L30W60H55 DALI



PRODUCT DATA



820-910



General Information

Order Code	820-910
Product Description	CYFELCO REC 2LNS 23W 3980LM 4000K L30W60H55 DALI
Application	Offices, shops, educational and public centres, etc.
Installation	Ceiling type exposed T-bar, plasterboard with accessories 590-001
Luminaire type	Recessed LED Luminaire - Office Compliant (UGR<19)
Light Source	LED modules SMD Vossloh-Schwabe
Number of light sources	2 pcs
Light Source Colour	4000K, cool white
Driver	Built-in Vossloh-Schwabe
Dimming	DALI
Energy Class	A++
Optical Risk	RG 0
Protection class	Class I
Ingress protection code	IP 20 [Finger-protected]
Mechanical impact protection code	IK03
Standards	2014/30/EU Electromagnetic Compatibility Directive 2014/35/EU Low Voltage Directive
CE mark	Yes
Warranty	5 years

Electrical Data

Input Power	26 W
Input voltage	220-240V
Input Frequency	50-60 Hz
Drive Current	350 mA
Power Factor	0.97

Mechanical Characteristics

Housing Material	Sheet steel 0,5mm
Surface Finish	White powder coating (RAL 9003)
Optical Cover	PMMA Optics (Wide 60°)

Initial Performance

Source Luminous Flux	3980 lm
Source Efficacy	172 lm/W
Initial Luminaire Luminous Flux	3781 lm
Initial Luminaire Efficacy	148 lm/W
Initial Corr. Colour Temperature (CCT)	4000 K
Initial Color Rendering Index (CRI)	>80 (Typ. 85)
Initial chromaticity	SDCM < 3
Unified Glare Rating (UGR)	UGR<19

Logistics

Net weight per piece	xxx kg
Gross weight per piece	xxx kg
Volume	0.33 m ³
Packing	1 pc per carton


Over Time Performance

Driver Service Life Time	100,000 hrs
LED Median Useful Life L80B10	60,000 hours

Application Conditions

Operating Temperature Range	-20 to +40 °C
Average Ambient Temperature	+25 °C

Dimensional Drawing



ELMASCO INDUSTRIES S.A.

Head Office : 44 K. Palama, 14343 N. Chalkidona, Athens, Greece

Production Plant : Ag. Adrianos, 21100 Nafplio, Greece

Email: elmasco@elmasco.eu

Tel : +30 210 2583100

Fax: +30 210 2583107

