



951-006



General Information

Order Code	951-006
Product Description	CYFELCO WP C258 RET LED
Application	Car Parks, warehouses, Factories, canopy lighting etc.
Installation	Fixation with ceiling using stainless steel suspension brackets
Luminaire type	Waterproof Light Fitting for T8 retrofit LED lamps
Light Source	T8 LED Tube
Number of light sources	2 pcs (not included)
Gear	--
Dimming	Not Dimmable
Standards	2014/30/EU Electromagnetic Compatibility Directive 2014/35/EU Low Voltage Directive 2011/65/EU RoHS Restrictions of Hazardous Substances Directive
CE mark	Yes
Warranty	2 years

Electrical Data

Input voltage	220-240 V
Input Frequency	50-60 Hz
Protection class	Class I

Mechanical Characteristics

Housing Material	Injection molded polycarbonate
Optical Cover	Injection molded polycarbonate
Ingress protection code	IP 65 [Dust penetration-protected, jet-proof]
Mechanical impact protection code	IK08
Dimensions LxWxH	1577x107x56 mm

Logistics

Packing	1 pc per individual box, 10 pcs per master carton
Net weight	1.32 kg
Gross weight	1.40 kg
Volume	0.0109286 m ³

Dimensional Drawing

