



809-025



General Information

Order Code	809-025
Product Description	CYFELCO BD 1X30W HPF
Application	Offices, shops, educational and public centres, etc.
Installation	Ceiling Surface Mounted Luminaire
Luminaire type	Traditional British Batten with Prismatic Diffuser
Light Source	T8 Fluorescent Tube
Number of light sources	1 pc (not included)
Gear	Vossloh-Schwabe Magnetic Ballast with Power Factor Correction (HPF)
Power Factor Correction	Capacitor 4.5 μ F
Dimming	Not Dimmable
Standards	2014/30/EU Electromagnetic Compatibility Directive
	2014/35/EU Low Voltage Directive
CE mark	Yes
Warranty	X years

Electrical Data

Lamp Power	30 W
Input voltage	220-240 V
Input Frequency	50-60 Hz
Protection class	Class I

Mechanical Characteristics

Housing Material	Sheet steel 0,5mm
Surface Finish	White powder coating (RAL 9003)
Optical Cover	PMMA Prismatic Diffuser
Ingress protection code	IP 40 [Finger-protected]
Mechanical impact protection code	IK03
Dimensions LxWxH	920x88x123mm

Logistics

Packing	1 pc per resistant carton
Net weight	xx kg
Gross weight	xx kg
Volume	Xx m ³

Dimensional Drawing

