



806-343



General Information

Order Code	806-343
Product Description	CYFELCO T8 REC 4X58 PD DALI
Application	Offices, shops, educational and public centres, etc.
Installation	Exposed T-bar, Plasterboard Ceilings
Luminaire type	Recessed Luminaire for T8 Lamps with Prismatic Diffuser
Light Source	T8 Fluorescent Tube
Number of light sources	4 pcs (not included)
Gear	Vossloh-Schwabe DALI Electronic Ballast (HF)
Dimming	DALI
Standards	2014/30/EU Electromagnetic Compatibility Directive 2014/35/EU Low Voltage Directive
CE mark	Yes
Warranty	X years

Electrical Data

Lamp Power	58 W
Input voltage	220-240 V
Input Frequency	50-60 Hz
Protection class	Class I

Mechanical Characteristics

Housing Material	Sheet steel 0,5mm
Surface Finish	White powder coating (RAL 9003)
Optical Cover	Prismatic PMMA
Ingress protection code	IP 20 [Finger-protected]
Mechanical impact protection code	IK03
Dimensions (mm)	

L	L1	L2	W	W1	W2	H	B
1497	1520	1532	597	573	553	81	47

Logistics

Packing	1 pc per resistant carton
Net weight	xx kg
Gross weight	xx kg
Volume	Xx m ³

Dimensional Drawing

